


LED SPOT DOWNLIGHT FAREO

Ideal use for hotel, restaurant, shops, offices and home lighting.



- Power 7-40 W 220-240 VAC 50/60Hz
- Luminous efficiency 85-100 lm/W
- SDCM 3 (MacAdam)
- Flicker free LED driver
- Temperature -15 °C +35 °C
- Lifespan: 50 000 L80/B50 (Ta=25 °C)
- Cover: IP20
- Options: ON/OFF/ TRIAC/ DALI/ KNOB / CASAMBI
- LED driver with high PF, low THD, small ripple and flicker free as standard option
- Different type of diffusers including prismatic diffuser UGR19 and wallwasher linear lens
- Color temperature range in standard on stock 2700K, 3000K and 4000K, or custom temperature colors from 2200K up to 6500K (on demand)
- High color rendering index over CRI90+ (STANDARD) or CRI80+/CRI95+ (on demand)
- Standard LED SMD technology
- Neverending line or custom shapes of luminaire system
- Separated high quality driver and LEDs for better heat management and optional service
- Aluminium body for better heat dissipation
- Lamp colors – Matt Black, Matt White (standard), RAL(option)
- Installation accessories - recessed

INSTALLATION



REFLECTOR



60°

SIZE



MODEL	POWER(W)	LUMENS SYSTEM(lm)	LUMENS SOURCE(lm)	SIZE(DxH) mm
FAREO XS	7	630	910	90x45
FAREO S	10	900	1300	105x45
FAREO M	15	1450	1950	130x45
FAREO L	20	1800	2600	165x45
FAREO XL	30	2700	3900	190x45
FAREO XXL	40	3600	5200	220x45

*3000K CRI90 Ta=25°C SDCM3

ORDER OPTIONS:

When ordering, please fill in the parameters in bracket in this order:

EXAMPLE: FAREO XS60 927W

MODEL	POWER	ANGLE	DIMMING	CRI	KELVIN	HOUSING	INSTALLATION
FAREO	XS	60	-	9	27	W	-
FAREO (FAREO)	7W(ø90mm) (XS) 10W(ø105mm) (S) 15W(ø130mm) (M) 20W(ø165mm) (L) 30W(ø190mm) (XL) 40W(ø220mm) (XXL)	60° (60)	ONN/OFF (-) DALI (DL) TRIAC (TR) KNOB (K) CASAMBI (CS)	CRI 90(9)	2700K(27) 3000K(30) 4000K(40)	Matt white(W) Matt black(B) RAL(RALXXXX)	Recessed (-)