

# LED OUTDOOR INGROUND POOL LIGHT DONO

LED architectural light



- Power 7-16 W 220-240VAC 50/60 Hz
- Luminous efficiency 110 lm/W
- SDCM 3 (MacAdam)
- Flicker free LED driver
- Temperature -15 °C +35 °C
- Lifespan: 50 000 L80/B50 (Ta=25 °C)
- Options: TRIAC/DALI/1-10V/DMX/SMART and different wireless options
- High color rendering index for spectacular light quality over CRI80+ (Standard), CRI90+ (on demand) or CRI95+ (on demand)
- Wide color temperature range from 2200K up to 6500K (on demand) with standard versions 2700K, 3000K and 4000K, SDCM 3 color accuracy
- Deep anti-glare structure ensures visual comfort which could be enhanced by extra accessory honeycomb or deep spot glare protection cover
- COB or High power LED version
- Ideal for architectural lighting of buildings, exterior installations or gardens
- IP66 and aluminium body for better heat dissipation
- Separated space for driver and LEDs for better heat management
- Lamp colors – Gray (standard), RAL(option)
- Wide option for reflectors, lenses or custom solution
- Different installation accessories
- Famous LED brands: CREE, LUXEON, NICHIA, OSRAM

MODEL	POWER(W)	LUMENS SYSTEM(lm)	LUMENS SOURCE(lm)
DONO 7	7	630*	945*
DONO 10	10	900*	1350*
DONO 12	12	1080*	1620*
DONO 16	16	1440*	2160*

\*3000K CRI90 Ta=25°C SDCM3

## ORDER OPTIONS:

When ordering, please fill in the parameters in bracket in this order:

### EXAMPLE: DONO M72.5 927GR



MODEL	SIZE	POWER	ANGLE	DIMMING	CRI	KELVIN	HOUSING
DONO	M	7	2.5	-	9	27	GR
DONO (DONO)	M (M) L (L)	7W for M (7) 10W for L (10) 12W for M (12) 16W for L (16)	2.5° (2.5) 3.5° (3.5) 5° (5) 10° (10) 15° (15) 20° (20) 30° (30) 40° (40) 1x10° (1x10) 1x40° (1x40) 1x60° (1x60) 10x60° (10x60)	ONN/OFF (-) TRIAC (TR) DALI (DA) 0/1-10V (110) ZIGBEE(ZG)	CRI 90(9) CRI 80(8)	2700K(27) 3000K(30) 4000K(40)	GREY (GR) WHITE (WT) BLACK (BK) Any RAL (RALXXXX)

# LED OUTDOOR INGROUND POOL LIGHT DONO

LAMP I A tech

LED architectural light

## DONO L



## DONO M

