

LED SPOT LIGHT


ADEON

Ideal use for hotel, restaurant, shops, offices and home lighting.




- Power 28-55W 220-240VAC 50/60Hz
- Luminous efficiency 85-100lm/W
- SDCM 3 (MacAdam)
- Flicker free LED driver
- Temperature -15°C +35°C
- Lifespan: 50 000 L80/B50 (Ta=25°C)
- Cover IP20
- Options: ON/OFF/ TRIAC/ DALI/ 1-10V/ ZIGBEE
- LED driver with high PF, low THD, small ripple and flicker free as standard option
- Different type of diffusers including prismatic diffuser UGR19 and wallwasher linear lens
- Color temperature range in standard on stock 2700K, 3000K and 4000K, or custom temperature colors from 2200K up to 6500K (on demand)
- High color rendering index over CRI90+ (STANDARD) or CRI80+/CRI95+ (on demand)
- Standard LED SMD technology
- Neverending line or custom shapes of luminaire system
- Separated high quality driver and LEDs for better heat management and optional service
- Aluminium body for better heat dissipation
- Lamp colors – Matt Black, Matt White (standard), RAL(option)
- Installation accessories - recessed



INSTALLATION



REFLECTOR



SIZE



MODEL	WATTS(W)	LUMENS SYSTEM(lm)	LUMENS SOURCE(lm)	SIZE(LxWxH) mm
ADEON 28W	28	2940*	3780*	165x165x111,62
ADEON 35W	35	3675*	4725*	165x165x111,62
ADEON 40W	40	4200*	5400*	165x165x111,62
ADEON 43W	43	4515*	5805*	165x165x111,62
ADEON 50W	50	5250*	6750*	165x165x111,62
ADEON 55W	55	5775*	7425*	165x165x111,62

*3000K CRI90 Ta=25°C SDCM3

ORDER OPTIONS:

When ordering, please fill in the parameters in bracket in this order:

EXAMPLE: HEDOS 2824 927G

MODEL	POWER	ANGLE	DIMMING	CRI	KELVIN	HOUSING	INSTALLATION
HEDOS	28	24	-	9	27	G	-
HEDOS (HEDOS)	28W (28)	24° (24)	ONN/OFF (-)	CRI 90(9)	2700K(27)	Matt gray(G)	Recessed installation (-)
	35W (35)	36° (36)	TRIAC (TR)		3000K(30)	Matt black(B)	
	40W (40)	48° (48)	DALI (DA)		4000K(40)	RAL(RALXXXX)	
	43W (43)	55° (55)	0/1-10V (110)				
	50W (50)	60° (60)	ZIGBEE(ZG)				
	55W (55)						