


LED MAGNETIC TRACK LIGHT ORCO

Ideal use for hotel, restaurant, shops, offices and home lighting.




- Power 3-13W 48 VDC 50/60 Hz
- Luminous efficiency 85-100 lm/W
- SDCM 3 (MacAdam)
- Flicker free LED driver
- Temperature -15 °C +35 °C
- Lifespan: 50 000 L80/B50 (Ta=25 °C)
- Cover IP20
- Options: ON/OFF/ TRIAC/ DALI/ 1-10V/ ZIGBEE
- LED driver with high PF, low THD, small ripple and flicker free as standard option
- Different type of diffusers including prismatic diffuser UGR19 and wallwasher linear lens
- Color temperature range in standard on stock 2700K, 3000K and 4000K, or custom temperature colors from 2200K up to 6500K (on demand)
- High color rendering index over CRI90+ (STANDARD) or CRI80+/CRI95+ (on demand)
- Standard LED SMD technology
- Neverending line or custom shapes of luminaire system
- Separated high quality driver and LEDs for better heat management and optional service
- Aluminium body for better heat dissipation
- Lamp colors – Matt Black, Matt White (standard), RAL(option)
- Installation accessories - surface


INSTALLATION



REFLECTOR



SIZE



MODEL	WATTS(W)	LUMENS SYSTEM(lm)	LUMENS SOURCE(lm)	SIZE(LxH) mm
25x40mm S	3	315*	405*	24x40
40x70mm M	8	840*	1080*	40x70
40x105mm L	13	1365*	1755*	40x105

*3000K CRI90 Ta=25°C SDCM3

ORDER OPTIONS:

When ordering, please fill in the parameters in bracket in this order:

EXAMPLE: ORCO S18 927B

MODEL	TYPE	ANGLE	DIMMING	CRI	KELVIN	HOUSING	INSTALLATION
ORCO	S	18	-	9	27	B	-
ORCO (ORCO)	25x40mm 5W (S)	18° (18)	ONN/OFF (-)	CRI 90(9)	2700K(27)	Matt white(W)	Surface (-)
	40x70mm 15W (M)	30° (30)	TRIAC (TR)		3000K(30)	Matt black(B)	
	40x105mm 30W (L)	45° (45)	DALI (DA)		4000K(40)	RAL(RALXXXX)	
			0/1-10V (110)				
			ZIGBEE(ZG)				