


LED ADJUSTABLE TRACK SPOTLIGHT TYRION

Precise light distribution is perfect for highlighting artworks, exhibitions, art galleries, showrooms, stores, and other commercial applications.




- Power 10-12 W 220-240VAC 50/60 Hz
- Luminous efficiency 85-100 lm/W
- SDCM 3 (MacAdam)
- Flicker free LED driver
- Temperature -15 °C +35 °C
- Lifespan: 50 000 L80/B50 (Ta=25 °C)
- Cover IP20
- Options: ON/OFF/ TRIAC/ DALI/ 1-10V/ ZIGBEE
- LED driver with high PF, low THD, small ripple and flicker free as standard option
- Different type of diffusers including prismatic diffuser UGR19 and wallwasher linear lens
- Color temperature range in standard on stock 2700K, 3000K and 4000K, or custom temperature colors from 2200K up to 6500K (on demand)
- High color rendering index over CRI90+ (STANDARD) or CRI80+/CRI95+ (on demand)
- Standard LED SMD technology
- Neverending line or custom shapes of luminaire system
- Separated high quality driver and LEDs for better heat management and optional service
- Aluminium body for better heat dissipation
- Lamp colors – Matt Black, Matt White (standard), RAL(option)
- Installation accessories - recessed


INSTALLATION



REFLECTOR



SIZE



MODEL	POWER(W)	LUMENS SYSTEM(lm)	LUMENS SOURCE(lm)	SIZE(LxH) mm
TYRION 10W	10	1050*	1350*	135x60
TYRION 12W	12	1280*	1620*	135x60

*3000K CRI90 Ta=25C° SDCM3

ORDER OPTIONS:

When ordering, please fill in the parameters in bracket in this order:

EXAMPLE: TYRION 1215 927W

MODEL	POWER	ANGLE	DIMMING	CRI	KELVIN	HOUSING	INSTALLATION
TYRION	12	15	-	9	27	W	-
TYRION (TYRION)	12W - STANDARD (12) 10W - for TRIAC (10) Custom (CXXW)	15° (15) 24° (24) 36° (36) 55° (55)	ONN/OFF (-) TRIAC (TR) DALI (DA) 0/1-10V (110) ZIGBEE(ZG)	CRI 70 (7) CRI 80 (8) CRI 90 (9) CRI 95 (95) CRI 98 (98)	2700K(27) 3000K(30) 4000K(40)	Matt white(W) Matt black(B) RAL(RALXXXX)	Surface (-)