


# LED DESIGN SQUARE LIGHT HADES




- Power 60-130W 220-240 VAC 50/60 Hz
- Luminous efficiency 85 lm/W
- SDCM 3 (MacAdam)
- Flicker free LED driver
- Temperature -15°C +35 °C
- Lifespan: 50 000 L80/B50 (Ta=25 °C)
- Cover IP20
- Options: ON/OFF/ TRIAC/ DALI/ 1-10V/ ZIGBEE
- LED driver with high PF, low THD, small ripple and flicker free as standard option
- Different type of diffusers including prismatic diffuser UGR19 and wallwasher linear lens
- Color temperature range in standard on stock 2700K, 3000K and 4000K, or custom temperature colors from 2200K up to 6500K (on demand)
- High color rendering index over CRI90+ (STANDARD) or CRI80+/CRI95+ (on demand)
- Standard LED SMD technology
- Neverending line or custom shapes of luminaire system
- Separated high quality driver and LEDs for better heat management and optional service
- Aluminium body for better heat dissipation
- Lamp colors – Matt Black, Matt White (standard), RAL(option)
- Installation accessories - surface, pendant



## INSTALLATION



## REFLECTOR



## SIZE



## ORDER OPTIONS:

When ordering, please fill in the parameters in bracket in this order:

### EXAMPLE: HADES M60927WS

MODEL	TYPE	*POWER	ANGLE	DIMMING	CRI	KELVIN	HOUSING	INSTALLATION
HADES	M	60	-	-	9	27	W	S
HADES (HADES)	600x600mm (M) 1200x600mm (L)	60W- for size S (60) 80W (80) 100W (100) 130W (130) 80W/50W (80/50) 100W/50W (100/50) 130W/50W (130/50)	120° (-)	ONN/OFF (-) TRIAC (TR) DALI (DA) 0/1-10V (110) ZIGBEE(ZG)	CRI 90(9)	2700K(27) 3000K(30) 4000K(40)	Matt white(W) Matt black(B) RAL(RALXXXX)	Surface (S) Pendant (P)

\*direct/indirect