

LED DESIGN ROUND LIGHT RONDO


LED DESIGN ROUND LIGHT

Design lighting for homes, galleries, shops, shops, commercial spaces and restaurants




- Power 35-70W 220-240 VAC 50/60 Hz
- Luminous efficiency 85 lm/W
- SDCM 3 (MacAdam)
- Flicker free LED driver
- Temperature -15°C +35 °C
- Lifespan: 50 000 L80/B50 (Ta=25 °C)
- Cover IP20
- Options: ON/OFF/ TRIAC/ DALI/ 1-10V/ ZIGBEE
- LED driver with high PF, low THD, small ripple and flicker free as standard option
- Different type of diffusers including prismatic diffuser UGR19 and wallwasher linear lens
- Color temperature range in standard on stock 2700K, 3000K and 4000K, or custom temperature colors from 2200K up to 6500K (on demand)
- High color rendering index over CRI90+ (STANDARD) or CRI80+/CRI95+ (on demand)
- Standard LED SMD technology
- Neverending line or custom shapes of luminaire system
- Separated high quality driver and LEDs for better heat management and optional service
- Aluminium body for better heat dissipation
- Lamp colors – Matt Black, Matt White (standard), RAL(option)
- Installation accessories - surface, pendant

INSTALLATION





REFLECTOR



120°

SIZE



MODEL	WATTS(W)	LUMENS SYSTEM(lm)	LUMENS SOURCE(lm)	SIZE(LxWxH) mm
RONDO 450 (S)	35	3675*	4725*	600x105
RONDO 600 (M)	65	6825*	8775*	720x105
RONDO 900 (L)	100	10500*	13500*	900x105
RONDO 1200 (XL)	125	13125*	16875*	1200x105

*3000K CRI90 Ta=25°C SDCM3

ORDER OPTIONS:

When ordering, please fill in the parameters in bracket in this order:

EXAMPLE: RONDO S927WS

MODEL	TYPE	ANGLE	DIMMING	CRI	KELVIN	HOUSING	INSTALLATION
RONDO	S	-	-	9	27	W	S
RONDO (RONDO)	450x105mm 35W (S) 600x105mm 65W (M) 900x105mm 100W (L) 1200x105 125W (XL)	120° (-)	ONN/OFF (-) TRIAC (TR) DALI (DA) 0/1-10V (110) ZIGBEE(ZG)	CRI 90(9)	2700K(27) 3000K(30) 4000K(40)	Matt white(W) Matt black(B) RAL(RALXXXX)	Surface (S) Pendant (P)